



## OAK YARROW

With a light stain lightening the tone of the natural oak raw-material, a luminescent golden touch has been added to Oak Yarrow. The oiled surface, brushed to soften the cracks and knots allows each board to demonstrate the natural wood grain of the material while still retaining the subtilty of this floor – in both its visual and tactile impression.

PRODUCT DETAILS	
Product type / Construction	Wood Flooring / 3-layer parquet
Article Number / EAN Code	131245200 / 7393969302487
Design / Wood Species	1-strip / Oak
Surface treatment /	Oil / Stained
Natural/Stained	
Design features	Microbevelled 4-sided, Brushed
Width x Length x Thickness	187 x 2000 x 13 mm
Weight per package / per	21 kg / 7.19 kg
m2	
Area per package / per	2.99 m <sup>2</sup> / 134.55 m <sup>2</sup>
pallet	
Grading	Dynamic
Joint	Woodloc® 5G
Installation method	Floating, Glue-down
Floor heating	Yes
Wear leayer material /	Hardwood / 2.6 mm
thickness	
Core material	Pine/Spruce lamella
Backside material	Spruce
Hardness (Brinell) value /	3,7 / 2.2 - 5.9
range	

<b>PRODUCT</b>	DETAILS
INODOCI	

LRV / LRV Std1 / LRV Std2	36 / 4.9 / 9.8	
Warranty	20 years	
TECHNICAL PROPERTIES		
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,14 W/mK
Thermal Resistance R-Value	!	.09 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD





## **DETAILED DESCRIPTION**

All naturally occuring wood colour variations allowed, from light to dark brown. The product includes large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.

## Other products in this collection









OAK YARROW OAK ASTER

OAK EDELWEISS OA